

Light

BESTNURSE

Flexible, breathable and comfortable slip-on sneaker

Designed to move you. This lightweight and stretchable slip-on sneaker feels like it was made just for you and helps you go the extra mile. Bestnurse's memory foam insole gives you advanced cushioning, while the heel energy absorption provides ultimate comfort and support for your feet. Engineered with ultimate breathability in mind, Bestnurse also keeps your feet dry, odor free and at a perfect temperature. Suitable for dry environments.

Upper	Mesh, Synthetic
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber (NBR)
Size range	EU 35-45 / UK 3.0-10.5 / US 3.0-11.5 JPN 21.5-29 / KOR 230-295
Sample weight	0.156 kg




Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Stretchable upper

Super elastic and stretchable textile for improved comfort and fit.



Vegan

Uses or contains no animal products.



WHT

Industries:

Medical

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	
Upper	Mesh, Synthetic			
	Upper: permeability to water vapor	mg/cm² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	N/A	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm² /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm²	N/A	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	N/A	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	N/A	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	N/A	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com