



Light

ECOFITZ S1P LOW

ECOFITZS1P

2nd generation of FITZ S1P with recycled upper for light applications

ECOFITZ S1P is made from recycled materials and is one of the most breathable safety shoes that you can put on your feet. With a slip-resistant outsole and a steel toe cap and midsole, this safety shoe offers reliable protection. It also features heel energy absorption and a removable foam footbed, promising long-lasting comfort.

| | |
|---------------|---|
| Upper | Knitted Recycled Textile |
| Lining | Recycled Mesh |
| Footbed | SJ foam footbed |
| Midsole | Steel |
| Outsole | PU |
| Toecap | Steel |
| Category | S1 P / SR, ESD, FO |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.613 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2022 |



BLK



GRY



NAV



Breathable upper
Increased moisture and temperature management for extended wearer comfort.

SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.

SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.

Industries:

Automotive, Construction, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Knitted Recycled Textile | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 37 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 88 | ≥ 15 |
| Lining | Recycled Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 54 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 288 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 91 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.47 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.51 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.20 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.24 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 408 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 29 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 17.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 19 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.